

80310

SB14150

**SAFETY DATA SHEET**

Page: 1

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION****Product identifier**

Trade name : Thermometer

**Recommended use of the chemical and restrictions on use**

Identified use : Thermometer

**Details of the supplier of the safety data sheet**C & A Scientific Co., Inc.  
7241 Gabe Court,  
Manassa, VA 20109-2434  
United States of America**Emergency telephone number**1-800-222-1222(American association of poison  
control centers)**Product Information**

1-703-330-1413

**E-mail:**

karla@cnascientific.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

This product is considered an article as defined by US OSHA Hazard Communication Standard (29 CFR 1910.1200, OSHA HazCom 2012) and it is not within the scope of the 29 CFR 1910.1200, as defined in this standard: "Article" means a manufactured item other than a fluid or particle, therefore this SDS is not required but provided as a courtesy in response to customer request and it contains valuable information critical to the safe handling and proper use of the product.

This product is considered safe under normal use conditions, however, this product is designed for thermometer application, it might cause hazards if this product is not used as directed or being abused. Please follow the recommendation from manufacturer or safety instruction on the label of products.

The following hazards assessment is carried out based on the internal component of thermometer under the worst-case scenario that it may be broken and cause exposure to users.

|                                                                 |                                       |
|-----------------------------------------------------------------|---------------------------------------|
| Flammable liquids                                               | : Category 3                          |
| Skin irritation                                                 | : Category 2                          |
| Specific target organ<br>systemic toxicity - single<br>exposure | : Category 3 (Central nervous system) |
| Aspiration hazard                                               | : Category 1                          |

# SAFETY DATA SHEET

Page: 2

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: Flammable liquid and vapor.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.

Precautionary Statements

: **Prevention:**  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ eye protection/ face protection.  
**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Substance

# SAFETY DATA SHEET

Page: 3

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

## Hazardous components

| Chemical name | CAS-No.   | Classification                                                                    | Concentration (%) |
|---------------|-----------|-----------------------------------------------------------------------------------|-------------------|
| KEROSENE      | 8008-20-6 | Flam. Liq. 3; H226<br>Skin Irrit. 2; H315<br>STOT SE 3; H336<br>Asp. Tox. 1; H304 | 100.00            |

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Call a physician or poison control center immediately.  
Keep patient warm and at rest.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.
- In case of eye contact : Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.
- If swallowed : If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended. If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.

## SECTION 5. FIREFIGHTING MEASURES

# SAFETY DATA SHEET

Page: 4

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Avoid spreading burning material with water used for cooling purposes.  
Do not use a solid water stream as it may scatter and spread fire.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.  
Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals.
- Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Prevent product from entering drains.

# SAFETY DATA SHEET

Page: 5

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Sweep up spilled material and absorbent with non-sparking tools.  
Decontaminate the area of the spill with a soap solution.

Other information : Comply with all applicable federal, state, and local regulations.

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
General industrial hygiene practices when using this product.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Store in a dry and well-ventilated place.  
Observe label precautions.  
No smoking.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

| Components | CAS-No.   | Value type<br>(Form of exposure) | Control parameters / Permissible concentration           | Basis        |
|------------|-----------|----------------------------------|----------------------------------------------------------|--------------|
| KEROSENE   | 8008-20-6 | TWA                              | 200 mg/m3<br>Non-aerosol<br>(as total hydrocarbon vapor) | ACGIH        |
|            |           | REL                              | 100 mg/m3                                                | NIOSH/GUID E |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

# SAFETY DATA SHEET

Page: 6

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

## Personal protective equipment

- Respiratory protection : Make sure adequate ventilation.  
Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.
- Hand protection : Wear protective gloves if necessary.
- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.  
Safety glasses
- Skin and body protection : Wear resistant gloves such as:  
Neoprene  
Nitrile rubber  
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse.  
Discard gloves that show tears, pinholes, or signs of wear.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Keep good industrial hygiene practices when using this product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Dark red liquid
- Physical state : Manufactured article contains liquid
- Odour : Characteristic
- Melting Point : 30 - 86°C
- Boiling Point : 180 - 356 °C
- Flash point : 120.00 - 190.00 °F / 48.89 - 87.78 °C
- Evaporation rate : 0.04  
n-Butyl Acetate
- Upper explosion limit : 5 %(V)

# SAFETY DATA SHEET

Page: 7

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

|                         |                                                              |
|-------------------------|--------------------------------------------------------------|
| Lower explosion limit   | : 0.7 %(V)                                                   |
| Vapour pressure         | : 1 - 10 mmHg (37.78 °C)                                     |
| Relative vapour density | : 4.5AIR=1                                                   |
| Relative density        | : 0.825 (60.00 °F)                                           |
| Density                 | : 0.825 g/cm3 (60 °F)                                        |
| Solubility(ies)         |                                                              |
| Water solubility        | : negligible (Liquid is soluble in other petroleum solvents) |
| Molecular weight        | : 185 g/mol                                                  |

## SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                                                                                                                           |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reactivity                         | : No decomposition if stored and applied as directed.                                                                                                                                     |
| Chemical stability                 | : Stable under recommended storage conditions.                                                                                                                                            |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. Vapours may form explosive mixture with air. Hazardous decomposition: Toxic fumes of: carbon monoxide carbon dioxide nitrogen oxides |
| Conditions to avoid                | : Contact with heat, sparks, open flames or other ignition sources.                                                                                                                       |
| Incompatible materials             | : Strong oxidizing agents                                                                                                                                                                 |

## SECTION 11. TOXICOLOGICAL INFORMATION

|                                                |                                                                                                                |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Information on likely routes of exposure       | : Inhalation<br>Skin absorption<br>Skin contact<br>Eye Contact<br>Ingestion                                    |
| Acute toxicity                                 |                                                                                                                |
| Not classified based on available information. |                                                                                                                |
| Acute oral toxicity                            | : LD 50 (Rat): > 5,000 mg/kg<br>Method: OECD Test Guideline 420                                                |
| Acute inhalation toxicity                      | : LC 50 (Rat): > 5.28 mg/l<br>Exposure time: 4 h<br>Test atmosphere: vapour<br>Method: OECD Test Guideline 403 |

# SAFETY DATA SHEET

Page: 8

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

## Skin corrosion/irritation

Causes skin irritation.

Remarks: May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Not classified based on available information.

Result: Slightly irritating to eyes

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

## Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

May cause drowsiness or dizziness.

## STOT - repeated exposure

Not classified based on available information.

## Aspiration toxicity

May be fatal if swallowed and enters airways.

## Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Ecotoxicology Assessment

Acute aquatic toxicity

: Not classified based on available information.

# SAFETY DATA SHEET

Page: 9

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

- Chronic aquatic toxicity : Not classified based on available information.
- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Test substance: WAF  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 1.4 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3 mg/l  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Water flea (Daphnia magna)): 0.89 mg/l  
Exposure time: 21 d  
End point: Reproduction Test  
Test Type: semi-static test  
Test substance: WAF  
Method: OECD Test Guideline 211
- Persistence and degradability**  
Biodegradability : Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F
- Bioaccumulative potential**  
No data available
- Mobility in soil**  
No data available
- Other adverse effects**  
No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

#### General advice

- : Contaminated absorbent may be deposited in a landfill in accordance with local, state and federal regulations.  
Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

# SAFETY DATA SHEET

Page: 10

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

Dispose in safe manner in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Handle empty containers with care because residual vapors are flammable.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

## SECTION 14. TRANSPORT INFORMATION

International transport regulations

### REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

#### U.S. DOT - ROAD

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | Kerosene | 3 | III |  |
|----|------|----------|---|-----|--|

#### U.S. DOT - RAIL

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | Kerosene | 3 | III |  |
|----|------|----------|---|-----|--|

#### U.S. DOT - INLAND WATERWAYS

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | Kerosene | 3 | III |  |
|----|------|----------|---|-----|--|

#### INTERNATIONAL MARITIME DANGEROUS GOODS

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | KEROSENE | 3 | III |  |
|----|------|----------|---|-----|--|

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | Kerosene | 3 | III |  |
|----|------|----------|---|-----|--|

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

|    |      |          |   |     |  |
|----|------|----------|---|-----|--|
| UN | 1223 | Kerosene | 3 | III |  |
|----|------|----------|---|-----|--|

Marine pollutant

no

Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15. REGULATORY INFORMATION

# SAFETY DATA SHEET

Page: 11

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

SARA 311/312 Hazards : Fire Hazard

SARA 313 : This material does not contain any chemical components with  
Component(s)SARA 313 known CAS numbers that exceed the threshold (De Minimis)  
reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know : Listed.

New Jersey Right To Know : Listed.

California Prop. 65 : This product does not contain a chemical known to the State  
of California to cause cancer.

The components of this product are reported in the following inventories:  
TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AUSTR : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PHIL : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories  
AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL  
(Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION

Further information

Revision Date: 11/08/2016

Full text of H-Statements referred to under section 3.

|      |                                               |
|------|-----------------------------------------------|
| H226 | Flammable liquid and vapor.                   |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation.                       |
| H336 | May cause drowsiness or dizziness.            |

### Disclaimer

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

# SAFETY DATA SHEET

Page: 12

Revision Date: 11/08/2016

SDS Number: RF-SDS379

Version: 1.0

Thermometer

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S. : Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level  
CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System